


: 5 * % 3

8OWUDVRIW 5HFRYHU\ %ULGJH



3, 11, 1*

3, 1	'(6&5, 37, 21
	, Q SX V A A Q
	, Q SX V A A Q
	2XWSXW \$ Q A R G H
	2XWSXW & A W K R G H


) HDWXUHV
 ‡* OD V DVVLY D W L S G F W L R Q
 ‡5HYH U R O W D J H 9
 ‡) R U Z D X G U H Q W
 ‡+ L J K X U & X U U H Q W D E L O L W \
 ‡' H V L J Q R G X U I D R X S S S O L F D W L R Q
 % H Q H I L W V
 ‡ & D V H % 3
 ‡ 7 H U P L G R O G H 3 B B 0 H 6 7'

0D[LPXP 5DWLQ Q G O H F W E K B D O F W H U L V W L F V

5DWLQ W V & D P E L M G H W S H U D Q D X U M K H U Z S H F L I L H G
 6LQJ O H S K D V H K Q O I H Z D V M U Q G X F O R D G H E D S D F L W E X H U G R O W H


3DUDPHWHU	6\PEROV	: 5 * % 3	8QLWV
0D[LPXP 5HSHWLWLYH 3HDN 5 9506	5 9506	VH 9ROWDJH	9
0D[LPXP 506 YROWDJH	9506		9
0D[LPXP '& %ORFNLQJ 9ROWDJH &			9
\$YHUDJH 5HFWLILHG 2XWSXW & X U U H Q W			\$
5HYHUVH 5HFRYHU\ 7LPH ,) \$, 5 \$, 55 \$	7UU		XV
3HDN)RUZDUG 6XUJH &XUUHQW +DOI 6LQH :DYH 6XSHULPSRV, H G R Q 5DWHG /RDG -('(& 0HWKRG		PV 6LQJOH	\$
, WUDW R O X V L Q B V W P V	, W		\$ 6
0D[LPX)RUZDUG WDW H \$	9)		9
0D[LPXP '& 5HYHUVH &XUUHQW #7\$ DW 5DWHG '& %ORFNLQJ 9ROWDJH #7\$		f & f &	\$
7\SLFDO -XQFWLR Q & D V S D F L W D Q & M H			S)
2SHUDWLQJ DQG 6WRUDJH 7H P S T W D W X U H 5DQJ H a			f &
1RWH0HDVX D M G +] D Q G S O L H H Y G H Y U R G H V R D J H &			

: 5 * % 3




7 F & DVH^R & 7 HPS

Current Derating




Reverse Voltage(V)

Typical Junction Capacitance



9 I, QVWDQWDQHR^R R^R V^R W^R W^R DUG


Typical Forward Voltage



9 5 5 HYHUVH^R R^R W^R W^R DJH

Typical Reverse Current

: 5 * % 3



GBP		
DIM.	MIN.	MAX.
A	14.20	14.70
B	3.30	3.60
C	10.20	10.60
D	13.80	14.40
d	1.40	1.70
E	1.80	2.20
F	0.80	1.10
G	3.71	3.91
H	0.30	0.55
I	1.22	1.42
J	0.76	0.86
K	2.7 x 45° (Typ)	
L	#	3°
M	#	2°

All Dimensions in millimeter